Cryopak[°] ion Technologies 💭 a TCP Company

iMINI USB pdf

iMINI USB pdf



- Plug & Play single use data logger
- No special software;
 - automatically opens as a PDF
- Preprogrammed to customer's specification
- Compact profile; weighs less than 14g
- Contained in waterproof pouch
- Large memory capacity; 7928 readings
- Five LEDs provide instant status

Features

The iMINI USB *pdf* single trip data logger generates a comprehensive PDF report without the need for proprietary software or interface. It comes pre-programmed; just press the start button and go. It is data logging made easy.

Four Alarm Thresholds



Now with expanded alarm thresholds, the user will be able to see a warning of temperature variances using the low and high settings as well as catastrophic levels with low low and high high settings, ensuring safe transport of perishable cargo.

bsi. NIST Traceable

Certifications

Cryopak Verification Technologies W a TCP Company

Specifications


iMINI USB pdf

cifications				
Description	Specifications			
Product Code	MS-ST-S-8			
Memory Options	8K, 7928 readings			
Program Interval	5 seconds to 17 hours			
Time Accuracy	±1 hour per year			
Sensors	Internal			
Temperature Range	-40 °C to +80 °C (-40 °F to +176 °F)			
Temperature Accuracy	$\pm 0.5 \ ^{0}C$ (-40 ^{0}C to -10 ^{0}C), $\pm 1 \ ^{0}F$ (-40 ^{0}F to +14 ^{0}F); $\pm 0.3 \ ^{0}C$ (-10 ^{0}C to +80 ^{0}C), $\pm 0.6 \ ^{0}F$ (+14 ^{0}F to +176 ^{0}F			
Resolution	0.1 ^o C (0.1 ^o F)			
Sensor Response Time	T90 of 5 minutes in moving air			
LCD Operating Range	N/A			
Alarm Thresholds	4 thresholds; 2 Red LEDs, 2 Blue LEDs			
Alarm Configuration	HIGH HIGH, HIGH, LOW & LOW LOW			
Bookmark	Yes, maximum 8			
Preprogram Option	Factory programmed			
Start Option	Push button and/or timer			
Auto Restart	N/A			
Start Delay	Yes, 1 minute to 99 days			
Stop Option	Yes, stop button (can be disabled) or timer			
Size	68mmx37mmx5mm (without sleeve) 81mmx52mmx5mm (with sleeve)			
Weight	14 g			
Case Material	Plastic sleeve			
Battery	3.0V			
IP Rating	IP 65			
Warranty	1 Trip			
Calibration	3 point NIST traceable calibration (optional)			
Accuracy Certificate	Upon request			
Other Certification	ISO9001:2008, CE, RoHS			
Shelf Life	1 Year			
Interface	USB			
Software	Console Plus			
Default File Format	PDF & CVT			
Data Export	TXT, CSV & CVT			
Security	N/A			



iMINI USB pdf

PDF Report (page1)



MS-CD-171-0999 09:01:59 21/06/2013

Device specification					
Product code	MS-ST-S-8				
Serial Number	MS-CD-171-0999				
H/W Version	Ver_1_37A				
Trip Remaining	No				
Description	Cryopak Ver Tech				
Battery	51%				
Original time zone	UTC: -5				
Start	20/06/2013 15:25:10				
Finish	21/06/2013 09:01:10				
Start Delay	15m				
Interval	60s				
Readings	1057				
Temperature Range	-40 to +80 °C				
High High Alarm	60.0 °C				
High Alarm	25.0 °C				
Low Alarm	0.0 °C				
Low Low Alarm	-20.0 °C				

Record

Cryopak Verification Technologies W a TCP Company

iMINI USB pdf

PDF Report (page2 & above)



MS-CD-171-0999 09:01:59 21/06/2013

Statistics

Highest	59.6 °C
Average	15.5 °C
Lowest	-31.7 °C
High High Alarm	Enabled
High Alarm	Activated
Low Alarm	Activated
Low Low Alarm	Activated
	Out of specification

Above High High Alarm Above High Alarm Below Low Alarm Below Low Low Alarm

Out of specifical
00h00m00s
07h56m00s
08h23m00s
04h50m00s

File Information					
File created	09:01:59 21/06/2013				
Security #	DCC1				

Index	Date	Time	°C	Index	Date	Time	°C
	00/00/00		10.5				
1	20/06/13		-18.5	56	20/06/13		-30.9
2		15:26:10	-18.5	57		16:21:10	-31.0
3		15:27:10	-18.5	58		16:22:10	-31.0
4	20/06/13		-18.5	59	20/06/13		-31.0
5	20/06/13		-18.7	60	20/06/13		-31.1
6		15:30:10	-19.1	61	20/06/13		-31.2
7		15:31:10	-19.6	62		16:26:10	-31.2
8	20/06/13		-20.2	63		16:27:10	-31.3
9	20/06/13		-20.9	64		16:28:10	-31.4
10	20/06/13		-21.5	65		16:29:10	-31.4
11	20/06/13		-22.1	66	20/06/13		-31.5
12	20/06/13	15:36:10	-22.6	67	20/06/13	16:31:10	-31.5
13	20/06/13	15:37:10	-23.2	68	20/06/13	16:32:10	-31.5
14	20/06/13	15:38:10	-23.6	69	20/06/13	16:33:10	-31.6
15	20/06/13		-24.1	70	20/06/13	16:34:10	-31.6
16	20/06/13	15:40:10	-24.5	71	20/06/13	16:35:10	-31.7
17	20/06/13	15:41:10	-24.9	72	20/06/13	16:36:10	-31.7
18	20/06/13	15:42:10	-25.3	73	20/06/13	16:37:10	-31.7
19	20/06/13	15:43:10	-25.6	74	20/06/13	16:38:10	-31.7
20	20/06/13	15:44:10	-25.9	75	20/06/13	16:39:10	-31.5
21	20/06/13	15:45:10	-26.1	76	20/06/13	16:40:10	-31.3
22	20/06/13	15:46:10	-26.5	77	20/06/13	16:41:10	-30.9
23		15:47:10	-26.7	78		16:42:10	-30.6
24	20/06/13	15:48:10	-27.0	79		16:43:10	-30.2
25	20/06/13	15:49:10	-27.2	80		16:44:10	-29.9
26	20/06/13		-27.4	81	20/06/13		-29.5
27		15:51:10	-27.6	82	20/06/13		-29.0
28	20/06/13		-27.8	83		16:47:10	-28.7
29	20/06/13		-28.0	84	20/06/13		-28.4
30		15:54:10	-28.1	85		16:49:10	-28.0