

## **Temperature Monitoring & Recording Data Logger**

### **Technical Specifications**



<b>Measurement</b>	Temperature Using (2) External Thermistor Sensor (#TR-0106)
<b>Temperature</b>	<u>Range:</u> -40°C to 110°C <u>Accuracy:</u> ±0.3°C (-20°C to 80°C); ±0.5°C (Other) <u>Resolution:</u> 0.1°C <u>Response Time:</u> About 190 Seconds to 90% <u>Thermal Time Constant:</u> About 75 Seconds
<b>Data Storage Capacity</b>	8,000 Samples/Readings
<b>Alarms</b>	High and Low Threshold Alarm Conditions with Email, Notification and External Contact Output Terminal for Buzzer, Siren, Lamp, or Electromagnetic Contactor
<b>External Output Terminal</b>	Alarm Output Terminal <u>Voltage When OFF:</u> AC/DC less than 50 Volts <u>Voltage When ON:</u> Less than 0.1 Amp <u>Resistance When ON:</u> About 35Ω
<b>Sampling Interval</b>	1,2,5,10,15,20,30 Seconds / 1,2,5,10,15,20,30,60 minutes (Total of 15 Choices)
<b>Recording Mode</b>	<u>Endless:</u> Overwrite Oldest Data when Capacity is Full
<b>LCD Display Items</b>	Current Readings / Recording Settings / Battery Life Warning / Over Measurement Range Warning / Amount of Recorded Data
<b>Power</b>	AC Adaptor (#AD-0638 - Included) Battery Backup: CR-2032 Lithium Coin Cell (Included) <b>NOTE: Battery is for Data Backup During Power Failure and Emergency Use Only. No Network Communications Available During Battery Operation.</b>
<b>Data Backup Communication Protocols</b>	Approx. 3 Months on Battery Only HTTP, SMTP, FTP, SNMP, DHCP and DNS <b>NOTE: SMTP Options: POP before SMTP, SMTP-AUTH</b>
<b>Communication Types</b>	<u>Wired LAN:</u> RJ45 Connector 100 Base-TX/ 10 Base-T Auto MDI/MDI-X <u>USB:</u> Cable Attached from Computer to Data Logger - For Setup Only
<b>OS Compatibility</b>	Windows 8 and 7 (32-bit and 64-Bit Versions), Vista and XP (32-Bit) <b>NOTE: For Windows 8, Software Should Be Used in "Desktop" Mode Only</b>
<b>Supported</b>	<u>Desktop:</u> IE 6.0+, Firefox 15.0+, Chrome 22.0+,

<b>Browsers</b>	Safari 6.0+ <u>Mobile</u> : Safari (iOS); Chrome (iOS, Android), Firefox (Android)
<b>Operating Environment</b>	<u>Temperature</u> : -10°C to 60°C <u>Humidity</u> : 90% RH or Less (No Condensation)
<b>Monitoring Functions</b>	<u>WebView</u> : View Data Graphs, Current Readings and Settings in Browser <u>WebStorage Service</u> : "Anytime, Anywhere" Complete Management of Recorded Data and Data Logger <u>Current Readings Monitor</u> : Management of Current Readings of all Registered Devices on Same Network <u>Mobile Devices</u> : WebView Software and T&D WebStorage Service compatible with Smart Phones and Tablets
<b>Standards Compliance</b>	CE, FCC
<b>Dimension</b>	55mm x 78mm x 37mm (Excluding Protrusions)
<b>Weight</b>	82 grams (Including Battery, Excluding Sensor)